NPA10S-12H
Monocrystalline Module


25 YEARS WARRANTY

CE

ELECTRICAL CHARACTERISTICS

Type	NPA10S-12H
Power Output(W)	10W
Voltage MPP Vmp(V)	17.00V
Current MPP Imp(A)	0.59A
Voltage Open Circuit Voc(V)	20.23V
Short Circuit Current Isc(A)	0.62A
Temperature Coefficient Of Voc	-(80±10)mV/°C
Temperature Coefficient Of Isc	(0.065±0.015)%/°C
Temperature Coefficient Of Power	-(0.5±0.05)%/°C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C


STC: 1000W/m² Irradiance, 25°C module temperature, AM1.5g spectrum according to EN 60904-3




MECHANICAL CHARACTERISTICS

Cells	Monocrystalline Silicon
Solar Cells Grade	Class A High Efficiency
Module Dimension(mm/in.)	365[14.37]x195[7.68]x23[0.91]
Weight(kg/lbs)	1.00[2.20]
Packing Information(mm/in.)	405[15.94]x280[11.02]x225[8.86]/(10pcs/ctn)

I-V CURVES (Irradiance: AM1.5, 1km/m²)





**Specications subject to technical changes and tests.*
NEWPOWA reserves the right of nal interpretation.

Dimensions in brackets are in inches.
Un-bracketed dimensions are in millimeters.
Unit: mm[in.]

Newpowa
BE WISE GO SOLAR

702-628-7600 sales@newpowa.com www.newpowa.com 1460 E Cedar St,Ontario,CA 91761