

NPA75S-12H

Monocrystalline Module



ELECTRICAL CHARACTERISTICS


Type	NPA75S-12H
Power Output[W]	75W
Voltage MPP Vmp[V]	17.0V
Current MPP Imp[A]	4.41A
Voltage Open Circuit Voc[V]	20.23V
Short Circuit Current Isc[A]	4.68A
Temperature Coefficient Of Voc	-[80±10]mV/°C
Temperature Coefficient Of Isc	[0.065±0.015]%/°C
Temperature Coefficient Of Power	-[0.5±0.05]%/°C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C

STC: 1000W/m² Irradiance, 25°C module temperature, AM1.5g spectrum according to EN 60904-3



MECHANICAL CHARACTERISTICS

Cells	Monocrystalline Silicon
Solar Cells Grade	Class A High Efficiency
Module Dimension[mm/in.]	850[33.46]x505[19.88]x30[1.18]
Weight[kg/lbs]	6.30[13.89]
Packing Information[mm/in.]	915[36.02]x555[21.85]x55[2.17]/(1pc/ctn)

I-V CURVES (Irradiance: AM1.5, 1km/m²)



*Specifications subject to technical changes and tests.
NEWPOWA reserves the right of final interpretation.



Dimensions in brackets are in inches.
Un-bracketed dimensions are in millimeters.
Unit: mm[in.]



702-628-7600



sales@newpowa.com



www.newpowa.com



1460 E Cedar St, Ontario, CA 91761



Newpowa
BE WISE GO SOLAR